Technical data sheet

GES9-3B service outlet with handle clamp

Item number: 7405077





Service outlet with handle clamp for up to 12 individual Modul 45 devices in 3 UT4 universal supports, use in trunking systems and system floors for indoor use.

Floor covering recess in the hinged cover pre-adjusted to 5 mm, if necessary adjustable to 10 mm.

Up to 9 installation devices with 50 mm central plate can be inserted. Service outlet with handle clamp, 3-compartment, for the installation of MT9 mounting support. Three type APMT5 cover plates can be installed. Floor covering recess in the hinged cover pre-adjusted to 5 mm, if necessary adjustable to 10 mm





Polyamide

Master data

Item number	7405077
Туре	GES9-3B U 7011
Description 1	Service outlet
Description 2	for universal mounting
Manufacturer	OBO
Dimension	264x264x67
Colour	Iron grey; RAL 7011
Material	Polyamide
Smallest sales unit	1
Unit of quantity	Piece
Weight	205 kg
Weight unit	kg/100 pc.

Technical data sheet

GES9-3B service outlet with handle clamp

117 1264





Dimensions Length Width 264 mm Height 67 mm Dimension h 73 mm

Number of installable devices	12	
Number of mounting boxes	3	
Version for	Square	
Cable outlet version	Swivellable cord outlet	
Floor covering protection frame	yes	
Floor care	Dry	
Seal installation option	no	
Floor height, min.	73 mm	
Suitable for raised floor installation	yes	
Suitable for screed-flush closed underfloor ducts	no	
Suitable for screed-covered underfloor ducts	yes	
Suitable for cavity floor installation	yes	
Suitable for wet care	no	
Suitable for underfloor box	250/350	
Suitable for underfloor ducts	yes	
Device support to accept mounting boxes	yes	
Length of external dimensions	264 mm	
Length of installation dimensions	244 mm	
With floor covering recess	yes	
Nominal size for device installation units	9	
Frame version	Carpet protection frame	
Protection rating (IP) when used	IP20	
Protection rating (IP) when unused	IP40	
Protection rating IK code	IK08	
Heavy-duty version	no	
Installation system type	UT4	
Vertical load, large area	to 5,000 N	
Vertical load, small area	to 3,000 N	

Technical data sheet

GES9-3B service outlet with handle clamp





Technical data	
Approvals	VDE
Opening mechanism	m Handle
Floor covering thick	kness 5 mm