Technical data sheet 45° bend 110 FS







45° bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 110 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used in indoor areas. Fastening material must be ordered separately.

CER

St

Steel

FS

Strip galvanized

Master data

Item number 6036300 Type RB 45 110 FS Description 1 45° bend Description 2 for cable tray, horizontal Manufacturer OBO Dimension 110x100 Material Steel Surface Strip galvanized Surface standard DIN EN 10346
Description 1 45° bend Description 2 for cable tray, horizontal Manufacturer OBO Dimension 110x100 Material Steel Surface Strip galvanized
Description 2 for cable tray, horizontal Manufacturer OBO Dimension 110x100 Material Steel Surface Strip galvanized
Manufacturer OBO Dimension 110x100 Material Steel Surface Strip galvanized
Dimension 110x100 Material Steel Surface Strip galvanized
Material Steel Surface Strip galvanized
Surface Strip galvanized
11 P 31
Surface standard DIN EN 10346
Smallest sales unit 1
Unit of quantity Piece
Weight 71.8 kg
Weight unit kg/100 pc.

Technical data sheet 45° bend 110 FS



Item number: 6036300

Dimensions 892 96 179

Width	100 mm
Height	110 mm
Plate thickness	0.8 mm
Dimension B	100 mm

Technical data

Bend (angle)	45°
Connector version	Integrated connector
Туре	Bend, rigid
Maintain electrical functions	no
Material thickness, floor plate	0.8 mm
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	yes
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	screwed/clamped
Recommended quantity of bolts	18 St.
Rail thickness	1.25 mm