Technical data sheet 45° bend 110 FT







45° bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 110 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.

CER

St

Steel



Hot-dip galvanised

Master data

6036332
RB 45 120 FT
45° bend
for cable tray, horizontal
OBO
110x200
Steel
Hot-dip galvanised
DIN EN ISO 1461
1
Piece
104.4 kg
kg/100 pc.

Technical data sheet

45° bend 110 FT

Item number: 6036332



Dimensions 688 196 279

Width	200 mm
Height	110 mm
Plate thickness	0.8 mm
Dimension B	200 mm

Technical data

Bend (angle)	45°
Connector version	Integrated connector
Туре	Bend, rigid
Maintain electrical functions	no
Material thickness, floor plate	0.8 mm
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	yes
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	screwed/clamped
Recommended quantity of bolts	20 St.
Rail thickness	1.25 mm