Technical data sheet

45° bend 60 FS

Item number: 6036106



45° bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 60 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used in indoor areas. Fastening material must be ordered separately.



CER

St

Steel

FS

Strip galvanized

Master data

6036106
RB 45 630 FS
45° bend
for cable tray, horizontal
OBO
60x300
Steel
Strip galvanized
DIN EN 10346
1
Piece
102.3 kg
kg/100 pc.
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1

Technical data sheet

45° bend 60 FS

Item number: 6036106



Dimensions 296 379

Width	300 mm
Height	60 mm
Plate thickness	0.8 mm
Dimension B	300 mm

Technical data

Bend (angle)	45°
Connector version	Integrated connector
Type	Bend, rigid
Maintain electrical functions	yes
Material thickness, floor plate	0.8 mm
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	yes
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	screwed/clamped
Recommended quantity of bolts	14 St.
Rail thickness	1.25 mm