
### **Technical data sheet**

Bend, angle-adjustable, 60 A4

Item number: 6037182





Angle-adjustable bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 60 mm. Adjustable angle  $0-90^\circ$ . Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.

# CERK

**A**4

Stainless steel

2E

Bright, treated

### Master data

6037182
RB W 660 A4
Adjustable bend
horizontal
OBO
60x600
Stainless steel
Bright, treated
1
Piece
410.9 kg
kg/100 pc.
F

## **Technical data sheet**

### Bend, angle-adjustable, 60 A4





# Dimensions 1120 595

Width	600 mm
Height	60 mm
Plate thickness	1.25 mm
Dimension B	600 mm
Dimension L	1,150 mm

### Technical data

Bend (angle)	Adjustable
Connector version	Integrated connector
Туре	Adjustable bend_complete
Maintain electrical functions	no
Material thickness, floor plate	1.25 mm
With cover	no
Mounting perforation in base	yes
NATO hole pattern	no
Change of direction	Horizontal
Rustproof steel, pickled	no
Side perforation	yes
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	Screwed
Recommended quantity of bolts	16 St.
Rail thickness	1.25 mm